

D-201E / D-401E

/
E1

- 30 (120 4E1) 1E1
- E1
- TDM: ISDN PRI, QSIG, CAS RJ-45
- - PCI
- 2E1, 4E1



- Legacy PBX/IVR
- (VoIP)
- Complex IVR Trees
- "Meet-Me" Bridge Conferencing
- VoIP Gateways (supports SIP, H.323 and IAX)





- Calling Card Platforms
- Voice/Data Router
- PRI Switch Compatibility – Network or CPE
- Asterisk IP-PBX

D-201E/D-401E		D-201E/D-401E	
Asterisk / IP-PBX	E1.	3,3	5 ,
PCI 32/33 MHz.		PCI, CPU	PCI-X
120	E1.		PCI.
D-201E/D-401E DAHDI/Zaptel.		ECM-128-OCT/ECM-064-OCT.	PCI

- E1/ 1 PCI,
- Asterisk®, FreeSwitch™, IP, IVR, VoIP-
- PSTN: ISDN PRI, QSIG, CAS.
- DSP
- PCI 5,0 3,3
- : 0 - 50 ° C.
- SyncPPP
- Frame Relay
- Cisco HDLC
- Multi-link PPP
- : HDB3, AMI, B8ZS
- : CRC-4, no CRC-4, ESF, SF, D4T1/E1
- 800
- 128
- PCI 2.2 32- /33
- Linux kernel 2.6.x
- Feature Group D
- E&M Wink
- a-Law, µ-Law
- Linear Modes Supported

120 , DSP VoIP . Octasic, G.168 ITU-T.

128 (1024 taps)

D-201		2E1, 60	2	E1
D-201E		2E1, 60	2	E1, G.168
D-401		4E1, 120	4	E1
D-401E		4E1, 120	4	E1, G.168